


Flex-E-Belt Technical Data

Operating Notes:

Due To The Single Steel Cable / Polyurethane Construction, This Series Offers a Flexible, Quiet, Lube Free Drive That Can Obtain Zero Backlash and Up To 7° Of Sprocket Misalignment.

32GBF Series

- 32 Pitch
- .0982 Circular Pitch
Cable Chain & Sprockets



- Cable Diameter 1/32 " Stainless Steel
- Ultimate Tensile 50 lbs., 9 lb / pin
- Recommended Maximum Operating Speed 376 ft./min.
- Recommended Operating Load 10 - 12 lbs
- Minimum Recommended Pulley Diameter 1/2" PD

33GBF Series

- 32 Pitch
- .0982 Circular Pitch
Cable Chain & Sprockets



- Cable Diameter .018 " Stainless Steel
- Ultimate Tensile 20 lbs., 7 lb / pin
- Recommended Maximum Operating Speed 376 ft./min.
- Recommended Operating Load 4 - 5 lbs
- Minimum Recommended Pulley Diameter 1/2" PD

31GBF Series

- 1/10 Pitch
- .1000 Circular Pitch
Belt & Sprockets



- Cable Diameter 1/32" Stainless Steel
- Ultimate Tensile 50 lbs., 9 lb / pin
- Recommended Maximum Operating Speed 376 ft./min.
- Recommended Operating Load 10-12 lbs
- Minimum Recommended Pulley Diameter 3/4" PD

24GBF Series

- 24 Pitch
- .1309 Circular Pitch
Dual Chain & Sprockets



- Cable Diameter 1/32" Stainless Steel
- Ultimate Tensile 50 lbs., 9 lb / pin
- Recommended Maximum Operating Speed 376 ft./min.
- Recommended Operating Load 10-12 lbs
- Minimum Recommended Pulley Diameter 3/4" PD