

# WAFER MAGNETIC CLUTCH

STYLE	TORQUE	RESPONSE TIME
<b>OUTPUT SHAFT BOTH ENDS</b>	<b>32 OZ. IN. MIN.</b>	<b>5.0 MS @ 28 V.D.C.</b>

Breakaway "Drag" torque Energized = .25 oz. in. Max. De-energized = .05 oz. in. Min.

STOCK NO.	A	B	C	D	E	F	G	I	J	K	L	M	N	O	P	Q
WMC-11-1	1.115	1.0000	.740	.3750	.1248	1.025	1.025	.061	.500	.180	.100	.060	.175	.120	.625	.300

STYLE	TORQUE	RESPONSE TIME
<b>OUTPUT SHAFT X ENDS</b>	<b>32 OZ. IN. MIN.</b>	<b>5.0 MS @ 28 V.D.C.</b>

Breakaway "Drag" torque Energized = .25 oz. in. Max. De-energized = .05 oz. in. Min.

STOCK NO.	A	B	C	D	E	F	G	I	J	K	L	M	N	O	P	Q
WMC-11-2	1.115	1.0000	.740	.3750	.1248	1.025	1.025	.061	.500	.180	.100	.060	.175	.120	.625	.300

STYLE	TORQUE	RESPONSE TIME
<b>OUTPUT SHAFT Y ENDS</b>	<b>32 OZ. IN. MIN.</b>	<b>5.0 MS @ 28 V.D.C.</b>

Breakaway "Drag" torque Energized = .25 oz. in. Max. De-energized = .05 oz. in. Min.

STOCK NO.	A	B	C	D	E	F	G	I	J	K	L	M	N	O	P	Q
WMC-11-3	1.115	1.0000	.740	.3750	.1248	1.025	1.025	.061	.500	.180	.100	.060	.175	.120	.625	.300

