

WAFER SPRING BRAKE

STYLE	TORQUE	RESPONSE TIME
OUTPUT SHAFT BOTH ENDS	12 OZ. IN. MIN.	7.0 MS @ 28 V.D.C.

Breakaway Torque = .20 oz. in. Max.

STOCK NO.	A	B	E	F	G	J	K	L	M	Q	TORQUE OZ. IN. Min.	RESPONSE TIME AT 28 V.D.C. (MS)
WSB-11-1	1.115 + .000 - .005	1.000 + .0000 - .0005	.1248 + .0000 - .0003	1.025 ± .005	1.025 ± .005	.500 ± .005	.180 (REF)	.100 ± .005	.060 + .003 - .000	.300 ± .020	12	7.0

STYLE	TORQUE	RESPONSE TIME
OUTPUT SHAFT X END	12 OZ. IN. MIN.	7.0 MS @ 28 V.D.C.

Breakaway Torque = .20 oz. in. Max.

STOCK NO.	A	B	E	F	G	J	K	L	M	Q	TORQUE OZ. IN. Min.	RESPONSE TIME AT 28 V.D.C. (MS)
WSB-11-2	1.115 + .000 - .005	1.000 + .0000 - .0005	.1248 + .0000 - .0003	1.025 ± .005	1.025 ± .005	.500 ± .005	.180 (REF)	.100 ± .005	.060 + .003 - .000	.300 ± .020	12	7.0

STYLE	TORQUE	RESPONSE TIME
OUTPUT SHAFT Y END	12 OZ. IN. MIN.	7.0 MS @ 28 V.D.C.

Breakaway Torque = .20 oz. in. Max.

STOCK NO.	A	B	E	F	G	J	K	L	M	Q	TORQUE OZ. IN. Min.	RESPONSE TIME AT 28 V.D.C. (MS)
WSB-11-3	1.115 + .000 - .005	1.000 + .0000 - .0005	.1248 + .0000 - .0003	1.025 ± .005	1.025 ± .005	.500 ± .005	.180 (REF)	.100 ± .005	.060 + .003 - .000	.300 ± .020	12	7.0

